

Cordless Cap Lamp

Lightweight series – for Petrochemical Environments and Surface Operations

Features



Three operating modes – Standard Focus, High-Beam Focus, Spread



Thin design means Cap Lamp fits behind visor and allows it to go up and down



Lightweight, comfortable and ergonomic



Rugged casing made from GERMAN FRAS material for rough handling & wide ambient temperature range



World's safest and most reliable Panasonic battery



Made from Top Brand, high quality components and parts



Product Specifications



IP Rating - IP67

Submersible in water up to 1m for 30min



Illumination

2800 Lx Standard Focus
5500 Lx High-Beam Focus



Charging Time

7 h



Running Time

13 h Standard Focus



Ambient Temperature

$-20^{\circ} \leq T_a \leq 40^{\circ}$



Weight

97 g



Certifications:

- Certificate #: IECEx TSA 19.0008
- Ex Marking: Ex ia op is IIB T3 Gb

Standard #:

- IEC 60079-0
- IEC 60079-11
- IEC 60079-28



Roobuck Pty Limited
Suite 6, 20 West Street
Brookvale, NSW 2100
Australia



+61 2 9938 1550



info@roobuck.com.au



roobuck.com.au

CB8T Charging Bank For 8 Cordless Cap Lamps



Features

- Portable, Wall Mountable
- Charging Connection Indicator
- Automatic over-load protection – cuts off that circuit when Cap Lamp battery is fully charged

Specifications

Input	240 VAC
Dimensions	33.4 x 18.2 x 6.6 cm
Weight	860 g

CB28T Charging Bank For 28 Cordless Cap Lamps

Features

- Wall Mountable
- Locking Bar for Cap Lamp safety
- Charging Connection Indicator
- Automatic over-load protection – cuts off that circuit when Cap Lamp battery is fully charged
- Space to attach identification label

Specifications


Input	240 VAC
Dimensions	84 x 60 x 11.5 cm
Weight	9 kg



Individual Chargers & Accessories



UCT: Single USB Charger



RCB-A

RCB-U

RCB-A/U: Angle Adjustable Brackets

RCB-A slides between the sides of the helmet bracket whereas RCB-U slides between the front & back of the helmet bracket.

